

TPRR 550

Technical data sheet



Description:	Rigid TPRR material with good flowability Can replace PP and engineering thermoplastics with demanding impact resistance
Applications:	Impact resistant products Suitable for outdoor products
Impact:	High stiffness with good impact strength

1. PRODUCT IDENTIFICATION AND SUPPLIER DETAILS

PRODUCT IDENTIFICATION


Product name	TPRR 550
Product description	TPRR (Thermoplastic recycled rubber) material consisting mainly of recycled plastics and recycled rubber.
Physical Appearance	Black solid plastic pellets, approximately 3 mm – 5 mm.
Recommended Use	Injection moulding and various industrial processes.

SUPPLIER DETAILS

Manufacturer	Ecorub AB (publ) Hökmark 114, 932 93 Lövånger, Sweden
Website	www.ecorub.se
Telephone	+46 70-399 71 31
E-mail	mattias.karlsson@ecorub.se

2. PRODUCT CHARACTERISTICS

PROPERTIES	TEST CONDITIONS	TYPICAL VALUES	TEST METHODS
Tensile Modulus	1 mm/min	710 Mpa	ISO 527-2/1A
Tensile Strength	50 mm/min	18 Mpa	ISO 527-2/1A
Elongation at Yield	50 mm/min	13 %	ISO 527-2/1A
Charpy Impact Strength	Notched A (23 °C)	9.5 kJ/m ²	ISO 179-1/1eA
Hardness	Shore D	59	ISO 48-4
Density	Method A	0.99 g/cm ³	ISO 1183-1
Melt Flow Rate	230 °C and 2.16 kg	5 g/10min	ISO 1133-1



To the best of our knowledge, the information for the presented product in this technical data sheet is accurate at the date of publication. However, the presented information is only typical properties/characteristics and is no warranty for the performance of the product in any specific purposes, but the customer is responsible to perform necessary tests of Ecorub's products to inspect the suitability for specific purposes. It is also the customer's responsibility to ensure that the products are handled and processed in a safe and appropriate manner in accordance with applicable legislation, recommendations and similar. Ecorub does not accept any liability when our products are used together with any other materials and/or products.